

CAT. N° 3 107 45



ADDITIONAL BATTERY CABINET - 2 X 20X12 AH - FOR KEOR S 6000-10000

Pack (number of units)	1
Volume (dm ³)	299,2
Weight (g)	193 400,00

Product characteristics

Additional battery cabinets

Battery cabinets

- Equipped with 2 x 20x12 Ah (for Keor S 6000-10000)

General characteristics

Keor S - On-line double conversion UPS (tower) - single phase

- For industrial environment (food industry, laboratories ...) or applications requiring long backup time (electro-medical ...)
- Installation: downstream power generators. Possibility to add batteries for extended autonomy. Parallel connection possible: up to 4 UPSs. Advanced management depending on the battery discharge level
- Sinusoidal output
- LCD screen
- Self-diagnosis
- Power factor: 0.9
- Integrated automatic bypass and maintenance bypass. Integrated slot for installing a communication interface for Ethernet network connection, to be ordered separately
- Cold Start Function. Microprocessor control
- Telephone line/Internet (RJ 11/RJ 45)
- Remote emergency shutdown function ("Emergency Power Off" - EPO). Equipped with 4 wheels for easy moving of the UPS

Documentation



Catalogue pages & additional information

- [Description page \(p.705\)](#)
- [Technical page \(p.706\)](#)