

BTICINO > Smart Home solutions > Connected Thermostat Smarther AC with Netatmo > Connected Thermostat flush mounting version




XW8003

The Smarther AC with Netatmo connected thermostat, together with the Home + Control APP, is a device which allows to precisely and accurately adjust and monitor the temperature in the rooms; all the programming and most of the functions can be easily and intuitively performed using the App. Thanks to its Wi-Fi connection, Smarther AC can be programmed and controlled remotely; it can also display the temperature, fan speed and humidity measured in the room. The temperature level can be set locally for manual operation and Boost mode can be activated. The Boost forces the switching on of the system for a limited time (15, 30 or 45 minutes) irrespective of the measured and programmed temperature. Smarther AC with Netatmo can also be controlled with Google, Amazon Alexa and Apple Home Kit voice assistants. Main features: - Power supply 110 to 240 Vac , 50/60 Hz; - 2 W max absorption; - Maximum cable section 1 x 1.5 mm²; - Operating temperature 5 to 40 °C; - 1-switching contact output free of 5(2)A potential. - Type of operation 1BU - Pollution index 2 - Rated pulse voltage 4 kV - Wireless device in compliance with 802.11b/g/n standard, frequency 2.4 - 2.4835 GHz, transmission power < 20 dBm. WEP/WPA/WPA2 safety protocol IPv4. - Radio link: short range communication, frequency 868MHz/915MHz, transmission power < 25mW e.r.p. Types of installation: - flush mounted, on boxes item 503E or 500 (for item 500 use the wall dowels) - plasterboard, on boxes item PB503 and PB502. White colour.

Technical features

Brand	BTicino
Rated voltage	110-240V a.c.
Rated power W	2
N° of modules	3
Height	87 mm
Width	126 mm
Depth	22,6 mm
Max section	1 x 1.5 mm ²

Documentation

 [Instruction Sheet](#)